



Better Air | Better Water | Better Living™

Commercial applications Data sheet

866-468-8247
 Ultravation.com
 sales@ultravation.com

RFQ or job name	
Wholesale firm	
Sales Representative	
Date :	
Ultravation Project manager	

Application type	Desired disinfection	Scope
Residential	Surface/ coil	Standard 60-65 % per pass
Commercial	Airstream	Medium 75-85% per pass
Industrial	Coil and airstream	High 95-99% per pass
Medical		

Please note: fan belts or wiring exposed within 3 feet of these devices must be shielded with a metal guard or foil tape.

AHU#	Make	Model	Coil Information		Stacked Coil	Center Drain	Drain pan per coil section	Distance drain pans extend on exit side	Distance from coil face to nearest obstruction? Describe	Type of System	Condition of coil	Air flow (assumption of 500 fpm if left blank)	Service access/door size
			Coil Size Inches __ Cm__										
			Width	Height	Y/N	Y/N	Y/N			Chilled water,DX, package unit, RTU	New, Cleaned, Bio growth		

Options:	
Door switch	
UVC monitor	
4-20 MA output signal	
CP control panel	

Options:	
Stainless steel	
Teflon encapsulate	
Window kit	
Lamp shields	

Specific target pathogen:

Specific job notes: